# Bulwark® CoolTouch®2 Dress Uniform Shirt SMU2

Arc Rating ATPV 9.0 calories/cm$^2$ (Khaki, Light Blue)

Arc Rating ATPV 10.1 calories/cm$^2$ (Navy)

FABRIC Flame-resistant CoolTouch®2 7-ounce, 48/37/15 modacryclic/lyocell/aramid (Khaki, Light Blue); 45/35/20 modacryclic/lyocell/aramid (Navy)
FEATURES Meets IL50 industrial laundry standards. Banded, topstitched, button-down collar. Placket front with button closure. Tailored sleeve plackets. Topstitched cuffs with button closures. Full side seam gussets.
STANDARDS This flame-resistant garment meets the requirements of NFPA2112, Standard on Flame-Resistant Garments for Protection of Industrial Personnel Against Flash Fire 2012 Edition; EN ISO 11612:2008, Protective Clothing Against Heat and Flame; EN 340:2003, Protective Clothing--General Requirements; and IEC 61482-2:2009, Live Working--Protective Clothing Against the Thermal Hazards of an Electric Arc.

**CARE INSTRUCTIONS**

Machine wash inside out with like colors. No bleach. No starch or fabric softeners. No products containing hydrogen peroxide. Tumble dry. Failure to launder properly could affect the flame resistance.

front

back

## HOW TO MEASURE




CHEST

With arms down at sides, measure around the upper body, under arms and over the fullest part of the chest.

NECK

Measure around the base of the neck, inserting a finger or two between the tape and neck for comfort.

## SIZE CHART

| | S | M | L | XL | 2XL | 3XL |
|---|---|---|---|---|---|---|
| Neck | 13 5/8-14 1/2 | 14 5/8-15 1/2 | 15 5/8-16 1/2 | 16 5/8-17 1/2 | 17 5/8-18 1/2 | 18 5/8-19 1/2 |
| Chest | 32 1/2-36 | 36 1/2-40 | 40 1/2-44 | 44 1/2-48 | 48 1/2-52 | 52 1/2-56 |
| Arm | 33 | 33 1/2 | 34 | 34 1/2 | 35 | 35 |

## COLOR INFORMATION

Khaki
PMS NO MATCH

Light Blue
PMS 646 C

Navy
PMS 433 C